

**RELAY MODULE FOR SMOKE-ALARM FIT-TR24V INCL. TRANSFORMER 24V DC WITH FAIL-SAFE FUNCTION FOR FIT(H) SERIES**



**FIT-TR24V Fire detector base coupling relay incl. transformer 24V DC and break contact for FIT(H) series**

<b>Fire detector base equipped with coupling relay and 24V DC transformer with anti-sabotage function (Fail-safe)</b>
<b>Power supply primary: 230V AC, 50Hz, 0.13A</b>
<b>Power supply secondary: 24V DC, 90mA, stabilized 2W</b>
<b>Break Contact is triggered in 3 ways:</b> <ul style="list-style-type: none"> <li>• When smoke is detected</li> <li>• If the power goes out</li> <li>• When the smoke detector is removed from the base plate</li> </ul>
<b>Cut outs: 2 x 20 mm, 2 x 28 mm, flexible cable entry, flat cable duct 250 mm</b>
<b>FIT-TR24V can be used to control automatic doors</b>
<b>Applicable to all brands of door closers</b>
<b>Maximum number of door closers to be connected per coupling relay: 1 piece</b>
<b>Can be combined with</b> <ul style="list-style-type: none"> <li>• Smoke detectors FIT-230(10) and FIT-230RF(L)</li> <li>• Heat detectors FITH-230(10) and FITH-230RF(L)</li> </ul>
<b>Mounting: surface mounted</b>
<b>Dimension: Ø 110 mm., height: 22 mm., weight: 80 grams</b>
<b>Colour: Off-white</b>
<b>Certification: CE</b>
<b>Guarantee: 5 years</b>
<b>Supplied including mounting material and 3 power cables 135 mm long, excluding the smoke detector</b>
<b>Packaging: cardboard box 13.5x13.5x2.5 cm, 48 pieces per outer carton</b>
<b>EAN-code FIT-TR24V: 8 713686 000685</b>