

LIFETIME 10 YEARS

WIRELESS RELAY FIRE ALARM NETWORK QR-NA 24V



QR-NA 24V wirelessly connectable smoke alarm relay

Compatible with ASD-10QR	and all brands of door closers and other devices that operate on 24 Volts
Connection to the control par	nel through a dry contact NO/NC
Creates a wireless network w	ith up to 23 smoke detectors
One button operation for all	modes
Self-recovery function	
LED-indication	
Possibility to amplify the sign	al by using an external antenna
Made in Europe	
Input voltage:	
QR-NA 24 Volt:	20V until 30V
RF Specifications:	
RF Frequency:	868,100 (<1% duty cycle)
RF power:	+14 dBm max.
RF range:	Up to 120 m. of open space
RF range with external anten	na: Up to 300 m. of open space
NO/NC specifications:	
Contact with active load:	1A/30VDC; 0.3A/125VAC
Max. switching power:	30W (1A/30VDC), 37.5VA (0.3A/125VAC)
In accordance with RoHS	
Operating temperature:	0°C tot + 55°C
Dimension:	L 115 mm, W 87 mm, H 27 mm
Weight:	76 grams
Lifetime:	up to 10 years
Guarantee:	5 years
EAN-code QR-NA 24V:	8713686002528